



PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/27/2017

Supersedes:02/16/2015

Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : PETRA HD OIL SYSTEM CLEANER 12 OZ. & 32 OZ.
Product code : 1011B, 1011B32

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Oil System Cleaner

1.3. Details of the supplier of the safety data sheet

Petra Automotive Products
11085 Regency Green Drive
Cypress, TX 77429
T 713-856-5700

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3 H226
Acute Tox. 4 (Inhalation:dust,mist) H332
Asp. Tox. 1 H304

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H332 - Harmful if inhaled

Precautionary statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust, fume, gas, mist, vapor spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P331 - Do NOT induce vomiting
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	30 - 50	Asp. Tox. 1, H304
Cyclohexanone	(CAS No) 108-94-1	30 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS No) 64742-52-5	10 - 30	Asp. Tox. 1, H304
4-Methyl-2-Pentanol	(CAS No) 108-11-2	1 - 5	Flam. Liq. 3, H226 STOT SE 3, H335

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Gloves.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply.
-----------------	--

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, vapor spray.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Take off immediately all contaminated clothing and wash it before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ MIST 8 HOURS
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ MIST 8 HOURS
Cyclohexanone (108-94-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm (Cyclohexanone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	200 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
4-Methyl-2-Pentanol (108-11-2)		
USA ACGIH	ACGIH TWA (mg/m ³)	104 mg/m ³ Skin
USA ACGIH	ACGIH TWA (ppm)	25 ppm Skin
USA ACGIH	ACGIH STEL (ppm)	40 ppm (Methyl isobutyl carbinol; USA; Short time value; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	100 mg/m ³ Skin
USA OSHA	OSHA PEL (TWA) (ppm)	25 ppm Skin
USA OSHA	OSHA PEL (STEL) (mg/m ³)	160 mg/m ³
USA OSHA	OSHA PEL (STEL) (ppm)	40 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Local exhaust ventilation, vent hoods.

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear appropriate mask.
Environmental exposure controls : Avoid release to the environment.
Consumer exposure controls : Avoid contact during pregnancy/while nursing.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Light yellow to yellow.
Odor : Petroleum-like odour. Solvent-like odour.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : > 100 °C
Flash point : 44 °C (Lowest Component)
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : 0.863
Solubility : Insoluble in water.
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : 1.92 cSt
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

VOC content : 33 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg body weight

Cyclohexanone (108-94-1)	
LD50 oral rat	1535 mg/kg (Rat; BASF test; Experimental value; 2650 mg/kg bodyweight; Rat)

4-Methyl-2-Pentanol (108-11-2)	
LD50 oral rat	2590 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	2870 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
IARC group	3

Cyclohexanone (108-94-1)	
IARC group	3

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if inhaled.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

Cyclohexanone (108-94-1)	
LC50 fish 1	527 - 732 mg/l (LC50; US EPA; 96 h; Pimephales promelas; Flow-through system; Fresh water; Experimental value)

4-Methyl-2-Pentanol (108-11-2)	
LC50 fish 1	360 mg/l (LC50; 24 h; Carassius auratus)
EC50 Daphnia 2	143.17 mg/l (LC50; 96 h; Daphnia magna)

12.2. Persistence and degradability

PETRA HD OIL SYSTEM CLEANER 12 OZ.	
Persistence and degradability	Not established.

Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Persistence and degradability	Not established.

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
Persistence and degradability	Not established.

Cyclohexanone (108-94-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	1.232 g O ₂ /g substance
Chemical oxygen demand (COD)	2.605 g O ₂ /g substance

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cyclohexanone (108-94-1)	
ThOD	2.605 g O ₂ /g substance
BOD (% of ThOD)	0.32 - 0.47 (Literature study)

4-Methyl-2-Pentanol (108-11-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	2.12 g O ₂ /g substance
Chemical oxygen demand (COD)	2.6 g O ₂ /g substance
ThOD	2.8 g O ₂ /g substance
BOD (% of ThOD)	0.76 (Calculated value)

12.3. Bioaccumulative potential

PETRA HD OIL SYSTEM CLEANER 12 OZ.	
Bioaccumulative potential	Not established.

Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Bioaccumulative potential	Not established.

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
Bioaccumulative potential	Not established.

Cyclohexanone (108-94-1)	
BCF other aquatic organisms 1	2.4 (BCF)
Log Pow	0.86 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

4-Methyl-2-Pentanol (108-11-2)	
Log Pow	1.57 (QSAR)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Cyclohexanone (108-94-1)	
Surface tension	0.034 N/m (20 °C)
Log Koc	log Koc, SRC PCKOCWIN v1.66; 1.18; Calculated value
4-Methyl-2-Pentanol (108-11-2)	
Surface tension	0.023 N/m

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, Cyclohexanone) (44 deg C c.c.), 3, III, Limited Quantity
ICAO/IATA (air):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, Cyclohexanone) (44 deg C c.c.), 3, III, Limited Quantity
IMO/IMDG (water):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, Cyclohexanone) (44 deg C c.c.), 3, III, Limited Quantity
Special Provisions:	<p>B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.</p> <p>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.</p> <p>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</p> <p>T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)</p> <p>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.</p> <p>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.</p>

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (Petroleum Distillates, Cyclohexanone) (44 deg C c.c.)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	<p>B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.</p> <p>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.</p> <p>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</p> <p>T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)</p> <p>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.</p> <p>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.</p>
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

14.3. Additional information

Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
-----------------------------	---

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

PETRA HD OIL SYSTEM CLEANER 12 OZ.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
-------------------------------------	--

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
-------------------------------------	---------------------------------

Cyclohexanone (108-94-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard Immediate (acute) health hazard
-------------------------------------	---

4-Methyl-2-Pentanol (108-11-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PETRA HD OIL SYSTEM CLEANER 12 OZ.

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

Cyclohexanone (108-94-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

4-Methyl-2-Pentanol (108-11-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class C - Oxidizing Material Class E - Corrosive Material
----------------------	--

EU-Regulations

4-Methyl-2-Pentanol (108-11-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Xn; R20

R10

Full text of R-phrases: see section 16

15.2.2. National regulations

Cyclohexanone (108-94-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECI (Korean Existing Chemicals Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Methyl-2-Pentanol (108-11-2)

15.3. US State regulations

PETRA HD OIL SYSTEM CLEANER 12 OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Cyclohexanone (108-94-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

4-Methyl-2-Pentanol (108-11-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Cyclohexanone (108-94-1)

State or local regulations

U.S. - Massachusetts - Right To Know List
New Jersey Right-to-Know
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H332	Harmful if inhaled
H335	May cause respiratory irritation

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

PETRA HD OIL SYSTEM CLEANER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability	: 2 Moderate Hazard
Physical	: 0 Minimal Hazard
Personal Protection	: B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.