

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/12/2015 : Version:

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : PETRA CONTACT CLEANER 10 OZ.

Product code : 9001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Contact Cleaner

### 1.3. Details of the supplier of the safety data sheet

Petra Oil Company

6100 West by Northwest Blvd. Ste. 190

Ste 190

Houston, TX 77040 T 713-856-5700

### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **Classification (GHS-US)**

Flam. Aerosol 1 H222 Repr. 2 H361 STOT SE 1 H370 STOT RE 2 H373

Full text of H-phrases: see section 16

### 2.2. Label elements

## **GHS-US** labeling

Signal word (GHS-US)

Hazard pictograms (GHS-US)





GHS02

: Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat,sparks,open flames,hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P307+P311 - If exposed: Call a poison center/doctor

P308+P313 - If exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell P321 - Specific treatment: See section 4.1 on SDS

P405 - Store locked up

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

local regional national

## 2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

03/06/2015 EN (English US) 1/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

## 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Naphtha (Petroleum), Hydrotreated Light	(CAS No) 64742-49-0	70 - 85	Asp. Tox. 1, H304
1,1-Difluoroethane, Liquefied, Under Pressure	(CAS No) 75-37-6	10 - 30	Liquefied gas, H280
n-Hexane	(CAS No) 110-54-3	0.72 - 3.6	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

The exact percentage is a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with

water for several minutes. Direct contact with the eyes is likely to be irritating. Obtain medical

attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath. Dizziness.

Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact : May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye

tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. May be harmful if swallowed and enters airways.

## 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

## 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol level 3.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

03/06/2015 EN (English US) 2/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust, fume, gas, mist, vapor spray.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the

leak, cut off the supply.

Methods for cleaning up : Store away from other materials.

## 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions.

Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Do not breathe dust,fumes,gas,mist,vapor spray.

Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with

mild soap and water before eating, drinking or smoking and when leaving work.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in

fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

## 7.3. Specific end use(s)

Follow Label Directions.

Hygiene measures

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Naphtha (Petroleum), Hydrotreated Light (64742-49-0)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

## 8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.

03/06/2015 EN (English US) 3/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Other information : Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to light yellow.
Odor : Solvent-like odour.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available

Melting point : -62 °C (Lowest Component)

Freezing point : No data available

Boiling point : 37 °C (Lowest Component)
Flash point : <-18 °C (Lowest Component)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.69

Solubility : Insoluble in water.
Log Pow : No data available
Log Kow : No data available

Viscosity, kinematic : 0.83 cSt

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

VOC content : 75 %

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

## 10.3. Possibility of hazardous reactions

Not established.

## 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

## 10.5. Incompatible materials

Strong acids. Strong bases.

## 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

03/06/2015 EN (English US) 4/1

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

_	according to Federal Register / Vol. 77, No. 30 / Worlday, Walch 20, 2012 / Rules and Regulations		
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)			
	LC50 inhalation rat (mg/l)	176 mg/l/4h (Rat; Literature study)	
	LC50 inhalation rat (ppm)	> 437500 ppm/4h Mortality in 2/6 at 43.75% and 1/6 at 38.3%. At $\geq$ 17.52% lethargy, laboured breathing, reduced responsiveness to sound were observed. At 6.64% only hyperaemia and shallow breathing were observed.	
	Methanol (67-56-1)		
	LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution	
	LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors	
	LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air	
	Skin corrosion/irritation	Not classified	
	Serious eye damage/irritation	Not classified	
	Respiratory or skin sensitization	Not classified	
	Germ cell mutagenicity	Not classified	
	Carcinogenicity	Not classified	
	Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
	Specific target organ toxicity (single exposure)	: Causes damage to organs.	
	Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.	
	Aspiration hazard	Not classified	
	Potential Adverse human health effects and symptoms	Based on available data, the classification criteria are not met.	
	Symptoms/injuries after inhalation	Shortness of breath. Dizziness.	
	Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.	
	Symptoms/injuries after eye contact	May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.	
	Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. May be harmful if swallowed and enters airways.	

## **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna; Locomotor effect)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

#### 12.2. Persistence and degradability

PETRA CONTACT CLEANER 10 OZ.		
Persistence and degradability	Not established.	
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)		
Persistence and degradability	Biodegradability in water: no data available.	
Methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance	
ThOD	1.5 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	0.8 % ThOD	
n-Hexane (110-54-3)		
Persistence and degradability	May cause long-term adverse effects in the environment.	
,	May cause long-term adverse effects in the environment.	

#### 12.3. **Bioaccumulative potential**

PETRA CONTACT CLEANER 10 OZ.	
Bioaccumulative potential	Not established.
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)	
Log Pow	0.75 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

03/06/2015 EN (English US) 5/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
n-Hexane (110-54-3)	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CF

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

## 14.3. Additional information

Other information : No supplementary information available.

## Overland transport

No additional information available

## Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

## Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

03/06/2015 EN (English US) 6/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>SECTION 15:</b>	Regulatory	information
15.1. US Federal	regulations	

PETRA CONTACT CLEANER 10 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard

# 1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory SARA Section 311/312 Hazard Classes Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard

## Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on the United States SARA Section 355 SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard

## 15.2. International regulations

## **CANADA**

PETRA CONTACT CLEANER 10 OZ.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)		
WHMIS Classification	Class A - Compressed Gas Class B Division 5 - Flammable Aerosol	
Methanol (67-56-1)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

## **EU-Regulations**

## Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2: R45 Muta.Cat.2; R46 Repr.Cat.3; R62 F+; R12 Xn; R20/21/22 Xn; R68/20/21/22

Full text of R-phrases: see section 16

#### 15.2.2. **National regulations**

## Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

## 15.3. US State regulations

PETRA CONTACT CLEANER 10 OZ.	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

03/06/2015 EN (English US) 7/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,1-Difluoroethane, Lic	uefied, Under Pressure (75-37-	6)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Methanol (67-56-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	
n-Hexane (110-54-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	
Naphtha (Petroleum), I	Hydrotreated Light (64742-49-0)	1		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	No	No	No	

## 1,1-Difluoroethane, Liquefied, Under Pressure (75-37-6)

## State or local regulations

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

## Methanol (67-56-1)

## State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

Other information : None.

Full text of H-phrases:

xt of H-phrases:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness

03/06/2015 EN (English US) 8/1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn

readilv.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



### **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 4 Severe Hazard Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

03/06/2015 EN (English US) 9/1