

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/11/2019 Supersedes:06/21/2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : PETRA AIR INTAKE CLEANER 6 OZ.

Product code : 2003

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

1.3. Details of the supplier of the safety data sheet

Petra Oil Company 11085 Regency Green Dr. Cypress, TX 77429 T 713-856-5700

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Aerosol 2 H223 H280 Press. Gas (Comp.) Acute Tox. 3 (Oral) H301 Acute Tox. 3 (Dermal) H311 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Repr. 2 H361 STOT SE 1 H370 STOT SF 3 H336 STOT RE 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)





GHS06





Version: 1.4

GHS02 GHS04

Signal word (GHS US) : Danger

Hazard statements (GHS US) : H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated H301+H311 - Toxic if swallowed or in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

11/10/2019 EN (English US) 1/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing

P307+P311 - If exposed: Call a poison center/doctor

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment: See section 4.1 on SDS

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Acetone	(CAS-No.) 67-64-1	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS-No.) 108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Methanol	(CAS-No.) 67-56-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	5 - 10	Press. Gas (Comp.), H280

The exact percentage is a trade secret.

First-aid measures after inhalation

SECTION 4: First aid measures

4.1. Description of first aid	measures
-------------------------------	----------

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get

medical advice/attention. Call a POISON CENTER or doctor/physician.

: Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call

a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Immediately call a poison center or doctor/physician.

Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain media

water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating.

milating.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin. Causes skin irritation.

Symptoms/effects after eye contact : Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.

11/10/2019 EN (English US) 2/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion

Toxic if swallowed. Swallowing a small quantity of this material will result in serious health

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove

ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released product, pump into suitable containers. Plug the leak

cut off the supply.

Methods for cleaning up : Store away from other materials

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use.

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust fumes gas mist vapor spray.

dust,fumes,gas,mist,vapor spray.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Always wash hands after handling the product.

Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse. Observe normal hygiene standards. Keep container tightly closed. Observe strict hygiene. Reduce/avoid exposure and/or contact. Observe very strict hygiene - avoid contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

11/10/2019 EN (English US) 3/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to

: Strong bases. Strong acids.

temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

Incompatible products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)				
USA ACGIH	ACGIH TWA (mg/m³)	75 mg/m³		
USA ACGIH ACGIH TWA (ppm)		20 ppm		
ISA OSHA OSHA PEL (TWA) (ppm)		200 ppm		
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm		
Carbon Dioxide, Liquefied,	Under Pressure (124-38-9)			
USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm		
USA ACGIH	ACGIH STEL (mg/m³)	54000		
USA ACGIH	ACGIH STEL (ppm)	30000 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³		
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm		
Methanol (67-56-1)				
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m ³		
USA ACGIH	ACGIH TWA (ppm)	200 ppm		
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m ³		
USA ACGIH	ACGIH STEL (ppm)	250 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm		
Benzene (71-43-2)				
USA ACGIH	ACGIH TWA (ppm)	1 ppm		
USA ACGIH	ACGIH STEL (ppm)	5 ppm		
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm		
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm		
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm		
Acetone (67-64-1)				
USA ACGIH	ACGIH TWA (mg/m³)	1188 mg/m³		
USA ACGIH	ACGIH TWA (ppm)	500 ppm		
USA ACGIH	ACGIH STEL (mg/m³)	1782 mg/m³		
USA ACGIH	ACGIH STEL (ppm)	750 ppm		

8.2. Exposure controls

Personal protective equipment

Appropriate engineering controls : Local e

: Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

2400 mg/m³

1000 ppm

: Gloves. Safety glasses. Avoid all unnecessary exposure.



OSHA PEL (TWA) (mg/m3)

OSHA PEL (TWA) (ppm)



Materials for protective clothing

: GIVE EXCELLENT RESISTANCE:

Hand protection

USA OSHA

USA OSHA

: Wear protective gloves.

11/10/2019 EN (English US) 4/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color

Freezing point : -78 °C (Lowest Component-Acetone)

Boiling point : 56.11 °C (Lowest Component-Acetone)

Flash point : -18 °C (Lowest Component-Acetone)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.82
Specific gravity / density : 0.82 g/cm³

Solubility : Poorly soluble in water.

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Heating may cause a fire. Heating may cause an explosion.

Oxidizing properties : No data available Explosion limits : No data available

9.2. Other information

VOC content : 45 %

Gas group : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

11/10/2019 EN (English US) 5/13

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified

Acute toxicity	: Not classified
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
ATE CLP (oral)	5580 mg/kg body weight
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
ATE CLP (oral)	100 mg/kg body weight
ATE CLP (dermal)	300 mg/kg body weight
ATE CLP (gases)	700 ppmV/4h
ATE CLP (vapors)	3 mg/l/4h
ATE CLP (dust, mist)	0.5 mg/l/4h
Benzene (71-43-2)	
LD50 oral rat	> 2000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LC50 inhalation rat (mg/l)	43.767 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
LC50 inhalation rat (ppm)	13700 ppm (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE CLP (vapors)	43.767 mg/l/4h
ATE CLP (dust, mist)	43.767 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – single exposure	: Causes damage to organs. May cause drowsiness or dizziness.
Specific target organ toxicity – repeated	: May cause damage to organs through prolonged or repeated exposure.
exposure	
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Toxic if swallowed. Toxic in contact with skin.
Symptoms/effects after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.
Symptoms/effects after eye contact	: Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue. Causes serious eye irritation.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Toluene (108-88-3)		
LC50 fish 1	5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value)	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
LC50 fish 1 35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)		
11/10/2010	EN (E. 11.110)	

11/10/2019 EN (English US) 6/13

Methanol (67-56-1)

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC50 fish 1	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)	
EC50 Daphnia 1	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-	
ErC50 (algae)	static system, Fresh water, Experimental value, Locomotor effect) 22000 mg/l (OECD 201: Alga, Growth Inhibition Test, 96 h, Pseudokirchneriella subcapitata,	
	Static system, Fresh water, Experimental value)	
Benzene (71-43-2)		
LC50 fish 1	5.3 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)	
EC50 Daphnia 1	10 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)	
ErC50 (algae)	100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
Acetone (67-64-1)		
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)	
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)	
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)	
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)	
TLM fish 2	> 1000 ppm (96 h; Pisces)	
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)	
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)	
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)	
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)	
<u> </u>	3400 mg/r (40 m, Chiorena Sp.)	
12.2. Persistence and degradability		
PETRA AIR INTAKE CLEANER 6 OZ.		
Persistence and degradability	Not established.	
Toluene (108-88-3)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance	
ThOD	3.13 g O ₂ /g substance	
BOD (% of ThOD)	0.69	
Carbon Dioxide, Liquefied, Under Pressure		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
Methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance	
ThOD	1.5 g O ₂ /g substance	
Benzene (71-43-2)		
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established.	
Biochemical oxygen demand (BOD)	2.18 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.15 g O ₂ /g substance	
ThOD	3.1 g O ₂ /g substance	
BOD (% of ThOD)	0.7	
Acetone (67-64-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.	
Riochemical oxygen demand (ROD)		
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance	
ThOD	2.2 g O ₂ /g substance	
BOD (% of ThOD)	(20 day(s)) 0.872	

EN (English US) 11/10/2019 7/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential			
PETRA AIR INTAKE CLEANER 6 OZ.			
Bioaccumulative potential Not established.			
Toluene (108-88-3)			
BCF fish 1	90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value)		
Log Pow	2.73 (Experimental value, 20 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)		
Log Pow	0.83 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Methanol (67-56-1)			
BCF fish 1	1 - 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)		
Log Pow	-0.77 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
Benzene (71-43-2)			
BCF fish 1	< 10 (OECD 305: Bioconcentration: Flow-Through Fish Test, 3 day(s), Leuciscus idus, Flow-through system, Fresh water, Experimental value)		
Log Pow	2.13 (Experimental value, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.		
Acetone (67-64-1)			
BCF fish 1	0.69 (Pisces)		
BCF other aquatic organisms 1	3		
Log Pow	-0.24 (Test data)		
Bioaccumulative potential Not bioaccumulative. Not established.			
12.4. Mobility in soil			
Toluene (108-88-3)			
Surface tension	27.73 N/m (25 °C)		
Ecology - soil	Low potential for adsorption in soil.		
Carbon Dioxide, Liquefied, Under Pressure (1	24-38-9)		
Ecology - soil	Not applicable (gas).		
Methanol (67-56-1)	TOTAL THE WAY		
Surface tension	0.023 N/m (20 °C)		
Log Koc	0.088 (log Koc, SRC PCKOCWIN v2.0, Calculated value)		
Ecology - soil	Highly mobile in soil.		
Benzene (71-43-2)			
Surface tension	0.029 N/m (20 °C)		
Log Koc	2.13 (log Koc, Calculated value)		
Ecology - soil	Low potential for adsorption in soil.		
Acetone (67-64-1)			
Surface tension 0.0237 N/m (20 °C)			
	1 · · · · · · · · · · · · · · · · · · ·		
2.5. Other adverse effects			

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

11/10/2019 EN (English US) 8/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. **UN** proper shipping name

Class (DOT)

Proper Shipping Name (DOT) : Aerosols

> Flammable, (each not exceeding 1 L capacity) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Emergency Response Guide (ERG) Number : 24-HOUR EMERGENCY INFORMATION: CHEMTREC (800) 424-9300

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location**

passenger vessel.

DOT Vessel Stowage Other 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

PETRA AIR INTAKE CLEANER 6 OZ.	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard

Toluene (108-88-3)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302

SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

Carbon blokide, Elquened, Onder 1 ressure (124-30-3)	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard
	Immediate (acute) health hazard

11/10/2019 EN (English US) 9/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on the United States SARA Section 355		
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard		
Benzene (71-43-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard
Fire hazard
Delayed (chronic) health hazard

15.2. International regulations

CANADA

SANADA					
PETRA AIR INTAKE CLEANER 6 OZ.					
WHMIS Classification	Class B Division 5 - Flammable Aerosol				
Toluene (108-88-3)	Toluene (108-88-3)				
Listed on the Canadian DSL (Domesti	C Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects				
Methanol (67-56-1)					
Listed on the Canadian DSL (Domesti	c Substances List)				
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects				
Benzene (71-43-2)					
Listed on the Canadian DSL (Domesti	c Substances List)				
Acetone (67-64-1)					
Listed on the Canadian DSL (Domestic Substances List)					
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects				

EU-Regulations

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Benzene (71-43-2)

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63 F; R11

T; R39/23/24/25 Xn; R20/21/22 Xn; R48/20 Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

11/10/2019 EN (English US) 10/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

Benzene (71-43-2)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

PETRA AIR INTAKE CLEANER 6 OZ.

	,				
U.S California - Proposition 65 - Carcinogens List		Yes			
U.S California - Proposition 65 - Developmental Toxicity		Yes			
U.S California - Proposition 65 - Reproductive Toxicity - Female		No			
U.S California - Propos Toxicity - Male	sition 65 - Reproductive	Yes U.S California - Proposition 65			
State or local regulations	}				
Toluene (108-88-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		
Carbon Dioxide, Liquef	ied, Under Pressure (124-38-9	9)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	No	No	No		
Methanol (67-56-1)	-				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
No	Yes	No	No		
Benzene (71-43-2)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	
Yes	Yes	No	Yes		
Acetone (67-64-1)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity -	U.S California - Proposition 65 - Reproductive Toxicity -	No significant risk level (NSRL)	

Toluene (108-88-3)

Yes

State or local regulations

U.S. - California - Proposition 65

U.S. - New Jersey - Special Health Hazards Substances List

Yes

New Jersey Right-to-Know

11/10/2019 EN (English US) 11/13

Male

Yes

Female

No

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List

Rhode Island Right to Know

U.S. - Michigan - Critical Materials List

U.S. - New Jersey - Environmental Hazardous Substances List

U.S. - Illinois - Toxic Air Contaminants

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65 New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

Benzene (71-43-2)

State or local regulations

U.S. - California - Proposition 65

U.S. - Pennsylvania - RTK (Right to Know) List

New Jersey Right-to-Know

Acetone (67-64-1)

State or local regulations

U.S. - California - Proposition 65

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-phrases:

H223	Flammable aerosol
H225	Highly flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause

temporary incapacitation or residual injury.


: 3 - Liquids and solids (including finely divided suspended NFPA fire hazard

solids) that can be ignited under almost all ambient

temperature conditions.

: 0 - Material that in themselves are normally stable, even NFPA reactivity

under fire conditions.



Hazard Rating

: 2 Moderate Hazard - Temporary or minor injury may occur Health

Flammability : 3 Serious Hazard : 1 Slight Hazard Physical

Personal protection : B

SDS US (GHS HazCom 2012) - TCC

11/10/2019 EN (English US) 12/13

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

11/10/2019 EN (English US) 13/13