

Petra Universal Long Life Antifreeze + Coolant Concentrate

PN4008G (1Gal) | PN400855 (55Gal)

Technical Data Sheet



Product Description:

Petra Universal Long Life Antifreeze + Coolant Concentrate features an extended life technology formulation which is recommended for use in all automobiles and light/medium duty trucks. It is free of amines, phosphate, borate, nitrite, and silicate and can be mixed with any color antifreeze/coolant in any vehicle. Its inhibitors provide maximum protection against damaging rust and corrosion, while preventing freeze-up and boil over at extreme temperatures.

Petra Universal Long Life Antifreeze + Coolant Concentrate meets the performance requirements of ASTM D3306, D4985 and with a complete flush and fill, this coolant will provide service life protection of up to 5 years or 150,000 miles*.

Features & Benefits:

- Specially formulated for use in all makes and models of cars and light/medium duty trucks using extended life coolant
- Compatible for use in any color antifreeze/coolant
- Protects all cooling system metals from rust and corrosion
- Meets the performance requirements of ASTM D3306, D4985
- Can be used in heavy-duty diesel commercial vehicle engines where low-silicate ethylene glycol based coolant is recommended**

*Protects all cooling system metals for up to 5 years/150,000 miles when a complete cooling system flush and fill is performed, and proper cooling system maintenance is followed. Always follow owner's manual for top-off requirements, change intervals, and specified maintenance.

**Check OEM requirements - may require the use of supplemental coolant additives (SCA)



Properties	ASTM Method	Concentrate	50/50	ASTM D3306 Limits
Appearance/Color	Visual	Yellow	Yellow	-
pH, 50 vol %	D1287	8.3	8.3	7.5-11.0
Specific gravity	D1122	1.122	1.066	1.110-1.145 ¹ /1.065min ²
Boiling point ³ , °F(°C)	D1120	325 (162.8)	299 (109.5)	226(108)min
Freezing point, °F(°C)	D1177	-	-37.8 (-38.8)	-34(-36.4)max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	Report ¹
Ash content, mass %	D1119	<5	<2.5	5max ¹ /2.5max ²
Chloride, ppm	D3634	<25	<25	25max
General Motors, Chrysler Ford, Asian & European Vehicle	For all makes, all models and all colors of antifreeze			

¹For concentrate product only, ²Ready to Use only, ³Unpressurized

Freeze/Boil Protection Chart		
Coolant/ Water Ratio	Protects From	
	Freezing Down to	Boiling Up to [†]
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

[†]Using a 15psi pressure cap



11085 Regency Green Drive • Cypress, Texas 77429
www.petraautoproducs.com • 1-888-Petra-61
info@petraautoproducs.com

follow us on:

