

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section 1. Product & Company Identification

1.1 Product Identifier

Product Name	: Petra Tire Seal - Commercial Grade
Product Number(s)	: 9002C
Synonyms	: Liquid gel
Recommended use	: Premium Tire Sealant/ Tire Casing Protector/ Puncture Repair

1.2 Company Identification: Details of the supplier of the Safety Data Sheet

Company Name Company Address : Petra Automotive Products, Inc. 11085 Regency Green Dr. Cypress, TX 77429 281.977.7400 : Business Hours: 214.280.3438 // After Hours: 844.912.6663

Emergency Telephone Number

Section 2. Hazard(s) Identification

2.1. Classification of the Substance or Mixture

GHS US Classification

Flammable Aerosol Category 1
Gases Under Pressure Compressed Gas
Skin Sensitization, Category 1

H222 Extremely flammable aerosolH280 Contains gas under pressure; may explode if heated.H317 May cause an allergic skin reaction

Full text of H- and EUH-statements: see section 16

2.2. Label Elements

GHS US Labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

Danger

Hazard statements (GHS US)

H222- Extremely flammable aerosol H280 - Contains gas under pressure; may explode if heated H317 - May cause an allergic skin reaction

Precautionary statements (GHS US)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use. P261 - Avoid breathing dust,fume,gas,mist,vapor spray P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves,protective clothing,eye protection,face protection P302+P352 - If on skin: Wash with plenty of soap and water P321 - Specific treatment: See section 4.1 on SDS P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse. P410+P403 - Protect from sunlight. Store in a well-ventilated place. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to appropriate waste disposal
	facility, in accordance with local, regional, national, international regulations.

2.3. Other Hazards

Other hazards which do not result in	Contains gas under pressure; may explode if heated. None under normal
classification	conditions.

2.4. Unknown Acute Toxicity (GHS US)

No data available.

Section 3. Composition/Information on Ingredients

3.1. Substances

Not Applicable

3.2. Mixtures

Name	Product Identifier	%	GHS US Classification
Distillates (Petroleum), Hydrotreated Light	(CAS-No.) 64742-47-8	70 – 85	Asp. Tox. 1, H304
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS-No.) 64742-52-5	1-5	Asp. Tox. 1, H304
SYN-ESTER(TM) GY-56	(CAS-No.) Proprietary	1-5	Not Classified
Carbon Dioxide, Liquefied, Under Pressure	(CAS-No.) 124-38-9	1-5	Press. Gas (Comp.), H280
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS-No.) 64742-52-5	0.685 – 1.37	Not Classified
WD 40 Type Fragance	(CAS-No.) Proprietary Mixture	<1	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Wrench Blaster Fragrance		<1	Eye Irrit. 2A, H319 Skin Sens. 1, H317 STOT SE 2, H371 Aquatic Acute 2, H401

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section 4. First Aid Measures

4.1. Description of First Aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).		
Inhalation	Cough. Allow affected person to breathe fresh air. Allow the victim to rest.		
Skin Contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment: See section 4.1 on SDS. Wash contaminated clothing before reuse.		
Eye Contact	Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.		
Ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.		
4.2. Most Important Symptoms and Effects, both Acute and Delayed.			
Symptoms/Effects	If you feel unwell, seek medical advice.		
Inhalation	Shortness of breath. May cause an allergic skin reaction.		

- **Skin Contact** May cause slight irritation . Red skin.
- **Eye Contact** May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

No additional information available

Section 5. Fire Fighting Measures		
5.1. Extinguishing Media		
Suitable Extinguishing Media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.	
Unsuitable Extinguishing Media	Do not use a heavy water stream.	
5.2. Special Hazards Arising from the Substance or Mixture		
Fire Hazard	Extremely flammable aerosol.	
Explosion Hazard	Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.	

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

5.3. Advice for Firefighters

Firefighting Instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.	
Protection During Firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.	
Other Information	Aerosol level 3.	
Section 6. Accidental Releas	e Measures	
6.1. Personal Precautions, P	rotective Equipment and Emergency Procedures	
General Measures	No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.	
6.1.1. For Non-Emergency P	ersonnel	
Protective Equipment	Gloves. Safety glasses.	
Emergency Procedures	Evacuate unnecessary personnel.	
6.1.2. For Emergency Respo	nders	
Protective Equipment	Equip cleanup crew with proper protection.	
Emergency Procedures	Ventilate area.	
6.2. Environmental Precautions		
Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.		
6.3. Methods and Material for Containment and Cleaning Up		
For Containment	Dam up the liquid spill. Plug the leak, cut off the supply. Contain released product, collect/pump into suitable containers.	
Methods for Cleaning Up	Store away from other materials.	
6.4. Reference to Other Sections		

See Heading 8. Exposure controls and personal protection.

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section 7: Handling and Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed	Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.	
Precautions for Safe Handling	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Avoid breathing dust,fume,gas,mist,vapor spray.	
Hygiene Measures	Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.	
7.2. Conditions for Safe Storage, Including Any Incompatibilities		
Technical Measures	Proper grounding procedures to avoid static electricity should be followed.	
Storage Conditions	Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.	
Incompatible Products	Strong bases. Strong acids.	
Incompatible Materials	Sources of ignition. Direct sunlight. Heat sources.	

Store in a well-ventilated place.

7.3. Specific End Use(s)

Follow Label Directions.

Storage Area

Revision Date: 04/18/24 (Original)

Section 8. Exposure Controls/Personal Protection

8.1. Control Parameters

Johnsen's Premium Penetrating Lubricant 15oz.			
No additional information available			
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)			
lo additional information available			
SYN-ESTER(TM) GY-56 (Proprietary)			
o additional information available			
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) JSA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	5 mg/m ³ MIST 8 HOURS		
USA - OSHA - Occupational Exposure Limits	USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) [1]	5 mg/m ³ MIST 8 HOURS		
Distillates (Petroleum), Hydrotreated Light (64742-47-8) USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	200 ppm 8 Hours		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA)	100 mg/m ³		
WD 40 TYPE FRAGRANCE (Proprietary Mixture)			
No additional information available.			
Wrench Blaster Fragrance			
No additional information available.			
Carbon Dioxide, Liquefied, Under Pressure (124-38-9) USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA ACGIH OEL TWA [ppm] ACGIH OEL STEL ACGIH OEL STEL [ppm]	9000 mg/m ³ 5000 ppm 54000 30000 ppm		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL (TWA) [1] OSHA PEL (TWA) [2]	9000 mg/m³ 5000 ppm		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA) NIOSH REL TWA [ppm] NIOSH REL (Ceiling) NIOSH REL C [ppm]	9000 mg/m ³ 5000 ppm 54000 mg/m ³ 30000 ppm		

8.2. Appropriate Engineering Controls

8.3. Individual Protection Measures/Personal Protective Equipment

Personal Protective Equipment	Gloves. Safety glasses. Avoid all unnecessary exposure.
Hand Protection	Wear protective gloves.
Eye Protection	Chemical goggles or safety glasses.
Respiratory Protection	Wear appropriate mask.
Personal Protective Equipment Symbol(s)	

Other Information

Do not eat, drink or smoke during use.

Section 9. Physical and Chemical Properties		
9.1. Information on Basic Physical and Chemical Properties		
Physical State	Gas	
Appearance	Liquid	
Color	Colourless to light yellow	
Odor	Kerosene	
Odor Threshold	No data available	
рН	No data available	
Relative Evaporation Rate (Butyl Acetate=1)	0.19	
Melting Point	No data available	
Freezing Point	No data available	
Boiling Point	222 – 247 °C	

SAFETY DATA SHEET

Revision Date: 04/18/24 (Original)

Flash Point	≥ 94.7 °C	
Auto-Ignition Temperature	No data available	
Decomposition Temperature	No data available	
Flammability	No data available	
Vapor Pressure	0.013 kPa	
Relative vapor density at 20 °C	4.5	
Relative Density	0.81	
Solubility	Insoluble in water	
Partition Coefficient N-Octanol/Water (Log Pow)	No data available	
Partition Coefficient N-Octanol/Water (Log Kow)	No data available	
Viscosity, Kinematic	1.92 cSt @40C	
Viscosity, Dynamic	No data available	
Explosive Properties	Heating may cause an explosion.	
Oxidizing Properties	No data available	
Explosion Limits	No data available	
9.1. Information on Basic Physical and Chemical Properties		
VOC Content	< 2 %	
Gas Group	Compressed gas	

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section 10. Stability and Reactivity

10.1. Reactivity

No additional information available

10.2. Chemical Stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of Hazardous Reactions

Not established.

10.4. Conditions to Avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible Materials

Strong acids. Strong bases.

10.6. Hazardous Decomposition Products

Toxic fume. . Carbon monoxide. Carbon dioxide.

Section 11. Toxicological Information 11.1. Information on Toxicological Effects Acute Toxicity (oral) Not classified

Acute Toxicity	Not classified
(dermal)	

Acute Toxicity Not classified (inhalation)

SYN-ESTER(TM) GY-56 (Proprietary)		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/m ³	
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
LD50 oral rat	> 5000 mg/kg body weight	
Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 Inhalation - Rat	> 5.28 mg/l/4h Based on lack of mortality and	
	systemic effects	

SAFETY DATA SHEET

Revision Date: 04/18/24 (Original)

Skin Corro	sion/Irritation	Not classified		
Serious Eye	e Damage/Irritation	Not classified		
Respiratory or Skin Sensitization		May cause an allergic skin reaction.		
Germ Cell I	Mutagenicity	y Not classified		
Carcinoger	nicity	Not classified		
	Distillates (Petroleu	m), Hydrotreated Heavy Naphthenic (64	1742-52-5)	
	IARC group		3 - Not classifiable	
Reproduct	ive Toxicity	Not classified		
STOT-Singl	e Exposure	Not classified		
	Wrench Blaster Frag	grance		
	STOT-Single Exposur	re	May cause damage to organs.	
STOT-Repe	ated Exposure	Not classified		
Aspiration	Hazard	Not classified		
Viscosity, K	Kinematic	1.92 mm²/s @40C		
	Adverse Human Based on available data, the classification criteria are not met.			
Symptoms	/Effects	If you feel unwell, seek medical advice.		
Symptoms Inhalation	/Effects After	Shortness of breath. May cause an allergic skin reaction.		
Symptoms contact	/effects after skin	May cause slight irritation . Red skin.		
Symptoms contact	/effects after eye	May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue.		

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section 12. Ecological information

12.1. Toxicity

 Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

 LC50 - Fish [1]
 Not established.

12.2. Persistence and Degradability

Johnsen's Premium Penetrating Lubricant 15oz.		
LC50 - Persistence and degradabilityFish [1]	35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal)	
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
Persistence and degradability	Not established.	
SYN-ESTER(TM) GY-56 (Proprietary)		
Persistence and degradability	Not established.	
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
Persistence and degradability	Not established.	
Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
Persistence and degradability	Not established.	
WD 40 TYPE FRAGRANCE (Proprietary Mixture)		
Persistence and degradability	Not established.	
Wrench Blaster Fragrance		
Persistence and degradability	Not established.	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
Persistence and degradability	Biodegradability: not applicable. Not established.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	

accumulative potential			
Johnsen's Premium Penetrating Lubricant 15oz.			
Bioaccumulative potential	Not established.		
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64	Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
Bioaccumulative potential	Not established.		
SYN-ESTER(TM) GY-56 (Proprietary)			
Bioaccumulative potential	Not established.		
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)			
Bioaccumulative potential	Not established.		
SYN-ESTER(TM) GY-56 (Proprietary)			
Bioaccumulative potential	Not established.		
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64	Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
Bioaccumulative potential	Not established.		
Distillates (Petroleum), Hydrotreated Light (64742-47-8)			
Bioaccumulative potential	Not established.		
WD 40 TYPE FRAGRANCE (Proprietary Mixture)			
Bioaccumulative potential	Not established.		
Wrench Blaster Fragrance			
Bioaccumulative potential	Not established.		
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4) Not established.		

12.4. Mobility In Soil

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Ecology - soil	Not applicable (gas).

12.5. Other Advers Effects

Effect on Global Warming	No known effects from this product.

Other Information Avoid release to the environment.

Section 13. Disposal Considerations 13.1. Waste Treatment Methods

Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional Information	Flammable vapors may accumulate in the container.
Ecology - Waste Materials	Avoid release to the environment.

Section 14. Transport Information

Department of Transportation (DOT)

In accordance with DOT

US DOT (ground) (DOT)	UN1950 Aerosols, 2.1
UN-No.(DOT)	UN1950
Proper Shipping Name (DOT)	Aerosols
Class (DOT)	2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
DOT Packaging Non Bulk (49 CFR 173.xxx)	None
DOT Packaging Bulk (49 CFR 173.xxx)	None

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

DOT Special Provisions (49 CFR 172.102)	N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	150 kg
DOT Vessel Stowage Location	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Emergency Response Guide (ERG) Number	126
Other information	No supplementary information available.
Transport by Sea	
UN-No. (IMDG)	1950
Proper Shipping Name (IMDG)	AEROSOLS
Class (IMDG)	2.1 - Flammable gases
Hazard labels (IMDG)	2.1 - Flammable gases
Transport by Sea	
UN-No. (IATA)	1950
Proper Shipping Name (IATA)	Aerosols
Class (IATA)	2.1 - Gases : Flammable

SAFETY DATA SHEET Revision Date: 04/18/24 (Original)

Section	ction 15. Regulatory Information			
15.1.US	5.1. US Federal Regulations			
	Johnsen's Premium Penetrating Lubricant 15oz.			
	SARA Section 311/312 Hazard Classes	Physical hazard - Gas under pressure		
	Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)			
	Listed on the United States TSCA (Toxic Substances Control Act) inventory			
	Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)			
	Listed on the United States TSCA (Toxic Substances Control Act) inventory			
	SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard		
	Distillator (Detrolours) Undrotwasted Light (64742, 47, 9)			
	Distillates (Petroleum), Hydrotreated Light (64742-47-8)			
	SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard		
		Delayed (chronic) health hazard		

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard ClassesSudden release of pressure hazardImmediate (acute) health hazard	

15.2. International Regulations

Johnsen's Premium Penetrating Lubricant 15oz.		
WHMIS Classification	Class B Division 5 - Flammable Aerosol	
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64	1742-52-5)	
Listed on the Canadian DSL (Domestic Substances List)		
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64	1742-52-5)	
Listed on the Canadian DSL (Domestic Substances List)		
Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
Listed on the Canadian DSL (Domestic Substances List)		

Revision Date: 04/18/24 (Original)

EU-Regulations

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

15.3. US State Regulations

Johnsen's Premium Penetrating Lubricant 15oz.

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA under 40 CFR 720.30.

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

15.2.2. National Regulations

Johnsen's Premium Penetrating Lubricant 15oz.()	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

SYN-ESTER(TM) GY-	56 (Proprietary)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleu	m), Hydrotreated Heav	vy Naphthenic (64742-5	2-5)	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

Distillates (Petroleum), Hydrotreated Light (64742-47-8)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

WD 40 TYPE FRAGR	ANCE (Proprietary Mix	ture)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

Wrench Blaster Frag	grance			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

Carbon Dioxide, Liq	uefied, Under Pressur	e (124-38-9)		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Carcinogens List	No significant risk level (NSRL)
No	No	No	No	

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)

State or Local Regulations

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York City - Right to Know Hazardous Substances List

U.S. - Pennsylvania - RTK (Right to Know) List

Section 16. Other Information


Other Information

None

Full Text of H-Phrases

H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H371	May cause damage to organs
H401	Toxic to aquatic life

NFPA Health Hazard	2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA Fire Hazard	4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA Reactivity	0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

2 Moderate Hazard - Temporary or minor injury may occur
4 Severe Hazard
0 Minimal Hazard
В

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product.

Disclaimer:

The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

Published by Petra Auto Products.



petraautoproducts.com